


EMD-482 Oxygen Transmitter

Product Specification Sheet

Configurable OEM Oxygen Transmitter, 2-wire loop



- Well Suited for OEM Installations
- Precision Fuel Cell Oxygen Sensor Technology
- Trace or Percent Configuration
- Measure Oxygen from 0.1ppm to 100%
- Updated Microprocessor Based Design
- Cost Effective, Compact & Low Maintenance
- Seamlessly integrates with PLC & DCS Systems

Configurations:

- User Selectable Ranges (Pre-Configured):
0 - 10ppm/100/1000ppm/1%/5%/10%/25%/100%
- Digital Push Buttons to Perform Local Span Cal
- Sensor Housings: H6 KF-40 or H3 Flow Through
- Optional Display without Backlight
- Many additional customized options available

Specifications:

Accuracy:	Calibration:	< 1% Full Scale Range* 2 -
Classification:	Dimensions	3 months or as needed
(PCB): Display: Temperature:	General Purpose	3.25 x
Temperature Compensation:	2.00 inch	Optional 0 - 50
Output: Sensor Housing:	deg C	Integral 4 - 20mA
Flow Sensitivity: Sensor	Optional, H6 or H3	0.5 -
Type: Warranty: Warranty:	5.0 SCFH	Precision Fuel
	Cell	12 Months Sensor 12
	Months	Electronics

*Accuracy at constant conditions



H3 Flow Through
Sensor Housing



H6 KF-40
Sensor Housing



Oxygen Sensor

Applications:

- InertGloveBox Systems
- Nitrogen and O2 PSA Generators
- Laboratories & Universities
- Beverage Grade CO2 Monitoring
- Air Separation Plants
- & Many Others

“Inquiry for Application Expertise”

Oxygen Transmitter:

The model EMD-482 oxygen transmitter combines a rugged electronic design with SSO2's precision oxygen sensors. The result is a highly reliable and cost effective compact design with an easy-to-use user interface.

The transmitter comes with a variety of options, which makes it configurable for a large array of applications. These options include custom ranges from 0 - 10ppm through 0 - 100%, a local display, sensor housings for flow through applications and ambient monitoring, as well as a variety of oxygen sensors. See the below ordering guide for complete options.

This unit is configured as a 2-wire loop powered device and is idea for integration with a PLC or DCS system. Output is non-isolated.

Oxygen Sensor Technology:

The oxygensensor used in the EMD-482 is based on the galvanic electrochemical fuel cell principal. All oxygen sensors are manufactured in house by Southland Sensing Ltd. under a strict quality program.

The standard cells are unaffected by other background gases such as H₂, He or Hydrocarbons. The acidic cells work well when acid gases such as CO₂ or Natural Gas are present. The sensors are self-contained and minimal maintenance is required - no need to clean electrodes or add electrolyte. The SSO2 precision oxygen sensors offer excellent performance, accuracy and stability while maximizing the expected life.

Oxygen Sensors:

TO2-1x PPM Oxygen Sensor: Trace Analysis, Standard TO2-2x PPM Oxygen Sensor: Trace Analysis, Acidic PO2-160 Percent Oxygen Sensor: Percent Analysis, Standard PO2-24 Percent Oxygen Sensor: Percent Analysis, Acidic Oxygen sensors should be periodically calibrated. Factory recommendation is every 2 - 3 months or as the application dictates. Sensors offer excellent linearity with an air calibration, or calibrate to a certified span gas to maximize accuracy.

Order Information:

RecordPartNumberwithselected options in Blank Indicated Area of Form

Model Number:

EMD-482 Oxygen Transmitter

Optional Display:

D Local Display with Backlight

X No Display, Blind

Area of Analyzers

T Trace Analysis

P Percent Analysis

Optional Sensor:

- | | |
|--|---|
| 1 Trace Analysis Standard (TO2-1x): | 0 - 10ppm, 0 - 100ppm, 0 - 1000ppm, 0 - 1%, 0 - 25% |
| 2 Trace Analysis Acidic (TO2-2x): | 0 - 10ppm, 0 - 100ppm, 0 - 1000ppm, 0 - 1%, 0 - 25% |
| 3 Percent Analysis Standard (PO2-160): | 0 - 1%, 0 - 5%, 0 - 10%, 0 - 25%, 0 - 100% |
| 4 Percent Analysis Acidic (PO2-24): | 0 - 1%, 0 - 5%, 0 - 10%, 0 - 25%, 0 - 100% |

Optional Sensor Housing:

- | | |
|---|--|
| 8 | H3 Flow Through with 1/8" Compression Tube Fittings |
| 4 | H3 Flow Through with 1/4" Compression Tube Fittings |
| 6 | H3 Flow Through with 6mm Compression Tube Fittings |
| K | H6 KF-40 Sensor Housing (Ideal for Ambient Monitoring or Glove Box Applications) |

Optional Factory Pre-Set 2nd Range:

If you want thefactory topre-set a 2nd range,please list the value here:

| (i.e. 0 - 10ppm, 0 - 100ppm, 0 - 10%, etc.)

Use This Part Number When Ordering

** For assistance when ordering, contact our inside sales specialist **

EMD-485 -